

|          |  |               |  |                       |  |                       |  |                                                |  |
|----------|--|---------------|--|-----------------------|--|-----------------------|--|------------------------------------------------|--|
| Справ. № |  | Перв. примен. |  | 2082 307518 1103 00 1 |  | 6 00 5105 241905 2802 |  | <div style="font-size: 2em;">✓</div> Ra6,3 (✓) |  |
|          |  |               |  |                       |  |                       |  |                                                |  |

Technical drawing of a mechanical part (flange) showing front and side views. The front view is an octagon with a central hole of diameter 80 mm. It has four 45-degree chamfers on the corners. Dimensions include a total width of 150 mm, a hole diameter of 80 mm with a tolerance of +0.07, and a thickness of 15 mm. Section A-A is indicated.

Side view of the flange showing its profile. It has a total height of 100 mm, a base width of 79.5 mm, and a top width of 150 mm. The top edge has a 45-degree chamfer. The thickness is 15 mm.

1. Маркировать Ч, клеймить К на дырке. Бирка Б по 2082 364000 ИТ1.

2. Остальные технические требования по СТП 2082-1222-2011.

|                            |  |  |  |  |
|----------------------------|--|--|--|--|
| 2082 506142 3013 00 9      |  |  |  |  |
| Бобышка                    |  |  |  |  |
| Сталь 20<br>ГОСТ 1050-2013 |  |  |  |  |

|       |       |         |
|-------|-------|---------|
| Лит.  | Масса | Масштаб |
| 12,05 | 1:2,5 |         |
| Лист  |       | 1       |

|          |      |           |       |      |
|----------|------|-----------|-------|------|
| Изм      | Лист | № докум.  | Подп. | Дата |
| Разраб.  |      | Миронова  |       |      |
| Пров.    |      | Говорунов |       |      |
| Т.контр. |      |           |       |      |
| Рук.     |      | Говорунов |       |      |
| Н.контр. |      | Мольков   |       |      |
| Утв.     |      |           |       |      |